
SKETCH #49 SHEET 1 OF 2 Typical Connectors to be Provided by the Customer for Serving a Single Point of Connection for Multiple Enclosed Service Entrance Conductors

SKETCH #49 SHEET 1 OF 2

NOT TO SCALE


INSULATED TYPE DISTRIBUTION BLOCK

I-1



NO. OF CNDCT.	CNDCT. RANGE KC MIL
4	750-1/0

I-2




	CABLE RANGE KCMIL	INSULATION OUTER DIAMETER		
DESCRIPTION		MIN.	MAX.	
4 POSITION	500-#4	350 KCMIL.	1.10 IN.	

BARE TYPE DISTRIBUTION BLOCK

B-1


THESE UNITS MAY BE USED FOR UNDERGROUND INSTALLATIONS ONLY WHEN INSULATING BARRIERS ISOLATE THE BARE CONNECTORS FROM OTHER PHASES, NEUTRAL, AND GROUND OR WHEN THE CONNECTORS ARE BOLTED TO A RIGID INSULATOR



SKETCH	8B
SKETCH	27
SKETCH	28
SKETCH	48

NO. OF MTG. HOLES	NO. OF CNDCT.	CNDCT. RANGE KCMIL	
6	4	250-6	
6	4	350-6	
6	4	500-2	
8	4	750-1/0	
10	6	750-1/0	
8	4	1000-350	
12	6	1000-350	

B-2



	CNDCT.
NO. OF	RANGE
CNDCT.	KCMIL
4	750-1/0
4	1000-350

REFERENCE: SKETCH 8B, SKETCH 27, SKETCH 28, SKETCH 48

RULES FOR ELECTRIC METER AND SERVICE INSTALLATIONS

PPL ELECTRIC UTILITIES CORPORATION

Rules: 5

Date: 8/12/11 **Engr:** MDB


REMSI_S049P1.dwg

SKETCH #49 SHEET 2 OF 2 Typical Connectors to be Provided by the Customer for Serving a Single Point of Connection for Multiple Enclosed Service Entrance Conductors

SKETCH #49 SHEET 2 OF 2

NOT TO SCALE

PRE-ASSEMBLED DISTRIBUTION BLOCK WITH INSULATING BARRIERS



CONN	CONNECTOR		PPL EU		CUSTOMER	
PPL EU (LINE SIDE)	CUSTOMER (LOAD SIDE)	WIRE RANGE KCMIL	OPENING PER CIRCUIT	WIRE RANGE KCMIL	OPENING PER CIRCUIT	NO. OF POLES
		350-#4 350-#4	1 1	2/0-#12 2/0-#12	2 2	2 3
	500-#4 500-#4	1	350-#4 350-#4	2 2	2	
		1000-250 1000-250 1000-250 1000-250	1 1 1	350-#4 350-#4 500-#4 500-#4	2 2 2 2	2 3 2 3
		2/0-#12 2/0-#12	2 2	2/0-#12 2/0-#12	2 2	2 3
		350-#4 350-#4	2 2	350-#4 350-#4	2 2	2 3
	500-#4 500-#4	2 2	500-#4 500-#4	2 2	2 3	
	500-#4 500-#4	2 2	2/0-#12 2/0-#12	6 6	2 3	
	350-#4 350-#4	2 2	2/0-#12 2/0-#12	6 6	2 3	
	1000-250 1000-250	1 1	2/0-#12 2/0-#12	6 6	2 3	

NOTES: (APPLY TO INSULATED, BARE, AND PRE-ASSEMBLED DISTRIBUTION BLOCKS):

- A. TYPICAL MANUFACTURERS NUMBERS ARE SHOWN. EQUIVALENT CONNECTORS FROM OTHER MANUFACTURERS MAY BE USED.
- B. ELECTRIC SUPPLY HOUSES MAY NOT STOCK. ALLOW TIME TO ORDER CONNECTORS FROM MANUFACTURER.
- C. ONLY ONE CONDUCTOR PER POSITION PERMITTED.
- D. SEE TABLE "APPROVED DISTRIBUTION CONNECTOR BLOCK TABLE FOR SKETCH 49" FOR LISTS OF PPL EU APPROVED MANUFACTURERS.

REFERENCE: SKETCH 8B, SKETCH 27, SKETCH 28, SKETCH 48

RULES FOR ELECTRIC METER AND SERVICE INSTALLATIONS

PPL ELECTRIC UTILITIES CORPORATION

Rules: 5

Date: 8/12/11 **Engr:** MDB